



NAPPA ANTINFORTUNISTICA

NAPPA ANTINFORTUNISTICA



www.professionepelli.com



Caratteristiche

Origine: Bovine europee

Concia: Concia al cromo e riconcia al cromo

Tintura: Tintura passante in botte con aniline solide alla luce

Look: Vitellone liscio per calzature antinfortunistiche - idrorepellente

Spessore: 1,8/2,0 mm

Rispetto delle regolamentazione sulle specifiche protette: Convenzione di Washington

Proprietà

Tenuta ad umido 50 cicli

Tenuta a secco 250 cicli

Tenuta al sudore alcalino 50 cicli

Resistenza alla luce

Prestazioni

Scala dei grigi min. 3

Scala dei grigi min. 3

Scala dei grigi min. 3

Scala dei blu min. 3

Technical features

Raw Origin: European bovines

Tannage: Tanning and re-tanning with chrome

Dyeing: Drum-Dyed trough with U.V. resistant anilines

Look: Smooth calfskin for safety - water-repellent footwear

Thickness: 1,8/2,0 mm

Respect of regulations on endangered species: Washington Convention

Property

Rubbing fastness 50 wet cycles

Rubbing fastness 250 dry cycles

Rubbing fastness 50 sweat cycles

Light fastness

Performance

Grey scale method min. 3

Grey scale method min. 3

Grey scale method min. 3

Blu scale method min. 3